



Sahara™ AnchorDeck™ (BU15)

At Sentry, we live and breathe synthetic roofing underlayment. So, when we claim that Sahara™ AnchorDeck™ is the only breathable synthetic roofing underlayment with multiple layers of waterproofing protection, you can trust that it was produced with state-of-the-art equipment by experts who excel in creating exceptional waterproof products.

Using Sahara™ AnchorDeck™ breathable underlayment allows for roof decks exposed to rain or snow during construction to dry after the primary roof has been installed. Breathability is vital in preventing mold, mildew, and potential structural damage. By specifying Sahara™ AnchorDeck™ breathable underlayment, you'll gain the competitive edge, giving your clients the confidence and security they demand to safeguard their valuable homes or buildings.

Sahara AnchorDeck's textured, slip-resistant walking surface offers excellent steep-slope walkability, productivity, comfort, and increased safety for roofers. Sahara™ AnchorDeck™ is designed for use under various roof types, including asphalt shingles, concrete tiles, synthetic shingles, primed cedar shakes, and metal roof systems, such as stone-coated steel shingles, metal panels, and metal accents. Sahara™ AnchorDeck™ meets all the necessary code requirements, including ASTM D226, ASTM D4869, ASTM D8257 and AC 188, as mandated by ICC-ES.

Features & Benefits

- Multiple layers of waterproofing protection
- 7 US perm rating (higher than felt)
- Outstanding strength to weight ratio
- Sure-Breathe technology maintains the breathability aspect of 15# felt
- Delivers all-temperature, all-weather performance, remaining pliable and easy to install in conditions ranging from -40°F to 240°F
- Minimizes stretching around fasteners with no blow-offs!
- Meets CAN/CSA A220.1 and CAN/CSA A123.3
- Class A fire rating - ASTM E108
- Meets ASTM D8257, ASTM D226 Types I & II and D4869 Types II & IV
- 90 days UV exposure
- Limited 20 year warranty



Test/Standard*

Typical Value

Tensile Strength ASTM D5034	MD 95 lbs (43 kg) CD 85 lbs (38.5 kg)
Tear Strength ASTM D4533	MD 18 lbs (8.16 kg) CD 16 lbs (7.26 kg)
Liquid Water Transmission ASTM D4869	Pass
Fire Rating ASTM E108	Class A
UV Exposure	3 Months
Temperature Range	-40° F - 240° F

Roll/Pallet Specs

Length per roll:	286' / 87 m
Width per roll:	42" / 1.2 m
Weight per roll:	28 lbs / 12.7 kg
Roll size:	10 sq / 93 m ²
Rolls per pallet/truck:	25
Pallet weight:	750 lbs / 340 kg

*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values ± 10 %. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures.

†When correctly installed as per installation instructions. All product installation instructions are available to download or view from our website: www.roofnado.com

SA BU15 SS MAR24

**Switch to Sahara™
and start saving on labor,
time & money.
Contact us today!
www.roofnado.com**

